



2018 Fassi F335A.2.25 e-dynamic

Knuckle Boom Cranes



Status:	Available				
Make	Model	Ton Rating	Boom Length	Stock Number	Serial Number
Fassi	F335A.2.25 e-dynamic	12.6765	47	BM-2626	3303-0424
Engine	HP	Transmission	Suspension	Miles	Hours
-	-	-	-	-	-

Features BASE - Base and lower part of the column in cast steel for perfect stress distribution and greater resistance. The absence of welding ensures that the crane offers excellent characteristics of durability to fatigue. BOOMS GUIDE - Extension booms guide shoes, with "forced" assembly to reduce vertical and horizontal clearance, ensuring greater durability. Special guide shoes material with high sliding degree and low greasing request. TANK - Plastic tank, particularly resistant to shocks and the corrosive action of any external element. LUBRICATION SYSTEM - Centralized lubrication system of the base to guarantee easier access for maintenance and control operations. OUTRIGGER - Hydraulically extendable outriggers also in "Extra wide" execution, with jointed outrigger rams plate and hoses fitted inside the stabilizer supports. Independent hydraulic distributor for the control of the outriggers; it can be also activated by radio control (option). Available as option manual or hydraulic tiltable outriggers. Optional VERSION C - Crane version with a shorter secondary arm, to allow a greater height of under-hook lifting. Offers the possibility to lift especially bulky and heavy loads vertically, near the column of the crane. Automatic hooking system for the positioning of the extension booms in transport position when crane is folded behind cab. WORK LIGHT - Powerful and versatile light that can be directed as required:



(continued from prior page)

helps you to work safely, even in conditions of poor natural light. Can be activated by means of the radio remote control pushbuttons. WINCH - Cable-operated lifting device equipped with an exclusive, patented mechanical, torque and end stop limiter system which avoids the risks resulting from direct and indirect overload applied to the winch itself. Anti-revolving cable and cable guide pulley to make easy the aligned winding of the cable on the winch drum.

Image Gallery



Price is Ex Works
 Sales Tax: Not included
 FET: Not Included

Terms: 15% Non-Refundable Deposit up front w/ balance due upon completion. Quote valid for 30 days, subject to prior sale. CraneWorks makes no claims with regard to roadability or permit requirements associated with the operation of this equipment. It is the owner's responsibility to verify that the purchased equipment meets local, state, and federal regulations.

NOTE: If roadability is of concern, CraneWorks will provide a weight study from the manufacturer, but we cannot guarantee its accuracy.